

Wireless connectivity Guide





Wi-Fi evohome Controller (ATC928G3000)



Wireless Cylinder Thermostat (CS92)

To bind a **Wireless Cylinder Thermostat (CS92)** to a **Wi-Fi evohome Controller (ATC928G3000)** to control a hot water cylinder...

On the **evohome Controller**

- 1 Press and hold  **SETTINGS** for 5 seconds
- 2 Press the green tick 
- 3 Press **SYSTEM DEVICES**
- 4 Press **STORED HOT WATER**
- 5 Press **ENABLED**
- 6 Press **HOT WATER SENSOR BINDING**

Evo centralenhed:

INDSTILLING (3 sek) og bekræft

SYSTEM ENHEDER

VARMTVANDSBEHOLDER / AKTIVERET

Tryk BIND knappen på føleren

On the **Wireless Cylinder Thermostat**

- 7 Press and hold the button for 5 seconds. The green light should come on and the red light should flash
- 8 Press the button again

You should receive a **SUCCESS** message on the evohome Controller and the LED on the Wireless Cylinder Thermostat should stop blinking and turn OFF. If not, go back and re-bind.

Put CS92A into binding mode by pressing and holding the button for 5 seconds, until the green light comes on and the red light flashes once every second. For best signal reception, the transceiver should be mounted in a location where there are no metal objects in a direct line between it and the master controller.