

SI-V32-M230-3POS

Technical Specifications Valve - VBI60.32-25T

- **Angular rotation**
- 90 °
- **Leakage rate**
- „Waterproof“ as per
- EN 60534-4 L/1,
- better than class 4
- **Leakage rate bypass**
- < 1 % of kv value
- **DN**
- 32
- **kvs**
- 25 m³/h
- **Medium**
- Cooling water, Chilled water, Water
- with anti-freeze,
- Low-temperature hot
- water, High-
- temperature hot water
- **Medium temperature**
- -10...120 °C
- **Permissible operating pressure**
- 1600 kPa
- **Material, valve body**
- Dezincification resistant
- hot-pressed brass (DZR),
- CW602N
- **Material, inside set**
- Dezincification resistant
- hot-pressed brass (DZR),
- CW602N, chromium-plated
- **PN class**
- PN 40
- **Connecting thread**
- Rp 1 1/4 "
- **GMA../GLB..9EΔpmax**
- 350 kPa
- **GLB..9EΔpmax**
- 350 kPa

Technical Specifications Actuator - GLB341.9E

- **Torque**
- 10 Nm
- **Angular rotation**
- 90 °
- **Power consumption**
- 5.8 VA, 1.9 W
- **Positioning time**
- 150 s
- **Cable length**
- 0.9 m
- **Positioning signal**
- 2-position/3-position
- **Spring return function**
- No
- **Degree of protection**
- IP54
- **Ambient temperature, operation**
- -32...55 °C
- **Dimensions (W x H x D)**
- 88 x 112 x 143 mm
- **Mounting position**
- Upright to horizontal
- **Operating voltage**
- AC 230 V
- **Position feedback**
- DC 0...10 V (GLB161.9E)
- **Auxiliary switch**
- 0