

SI-V40-M230-3POS

Technical Specifications Valve - VBI60.40-49T

- **Angularrotation**
 - 90 °
 - **Leakage rate**
 - „Waterproof“ as per
 - EN 60534-4 L/1,
 - betterthanclass 4
 - **Leakage rate bypass**
 - < 1 % of kvsvalue
 - **DN**
 - 40
 - **kvs**
 - 49 m³/h
 - **Medium**
 - Coolingwater, Chilledwater, Water
 - with anti-freeze, Low-temperaturehot water, High-temperaturehot water
 - Medium temperature
 - -10...120 °C
 - Permissibleoperating pressure
 - 1600 kPa
 - **Material, valvebody**
 - Dezinificationresistant hot-pressedbrass(DZR), CW602N
- **Material, insideset**
 - Dezincificationresistant hot-pressedbrass(DZR), CW602N, chromium-plated
 - **PN class**
 - PN 40
 - **Connectingthread**
 - Rp 1½ "
 - **GMA../GLB..9EΔp_{max}**
 - 350 kPa
 - 350 kPa
 - **GLB..9EΔp_{max}**
 - 350 kPa

Technical Specifications Actuator - GLB341.9E

- **Torque**
 - 10 Nm
- **Angular rotation**
 - 90 °
- **Power consumption**
 - 5.8 VA, 1.9 W
- **Positioning time**
 - 150 s
- **Cable length**
 - 0.9 m
- **Positioning signal**
 - 2-position/3-position
- **Spring return function**
 - No
- **Degree of protection**
 - IP54
- **Ambient temperature, operation**
 - -32...55 °C
- **Dimensions (W x H x D)**
 - 88 x 112 x 143 mm
- **Mounting position**
 - Upright to horizontal
- **Operating voltage**
 - AC 230 V
- **Position feedback**
 - DC 0...10 V (GLB161.9E)
- **Auxiliary switch**
 - 0