

SI-V50-M230-2POS

Technical Specifications Valve - VBI60.50-73T

- **Angular rotation**
- •90 °
- **Leakage rate**
- •„Waterproof“ as per
- •EN 60534-4 L/1,
- •better than class 4
- **Leakage rate bypass**
- •< 1 % of kvs value
- **DN**
- •50
- **kvs**
- •73 m³/h
- **Medium**
- •Cooling water, Chilled water, Water
- •with anti-freeze,
- •Low-temperature hot
- •water, High-temperature hot water
- **Medium temperature**
- •-10...120 °C
- **Permissible operating pressure**
- •1600 kPa
- **Material, valve body**
- •Dezincification resistant
- •hot-pressed brass (DZR), CW602N
- **Material, inside set**
- •Dezincification resistant
- •hot-pressed brass (DZR), CW602N, chromium-plated
- **PN class**
- •PN 40
- **Connecting thread**
- •Rp 2 "
- **GMA../GLB..9EΔp max**
- •350 kPa
- **GLB..9EΔp max**
- •350 kPa

Technical Specifications Actuator - GMA321.9E

- **Torque**
- •7 Nm
- **Angular rotation**
- •90 °
- **Power consumption**
- •7 VA, 4.5 W
- **Positioning time**
- •Opening with motor: 90 s, Closing with spring: 15 s
- **Positioning signal**
- •2-position
- **Spring return function**
- •Yes
- **Degree of protection**
- •IP54
- **Ambient temperature, operation**
- •-32...55 °C
- **Dimensions (W x H x D)**
- •93 x 112 x 184 mm
- **Mounting position**
- •Upright to horizontal
- **Operating voltage**
- •AC 230 V
- **Position feedback**
- •DC 0...10 V (GMA161.9E)