

High-flow Thermostatic Valve [V2000LX](#)

Approvals Keymark certified and tested to EN 215

EN215 certified Yes

Medium type water or water-glycol mixture according to VDI 2035

Port connection internal threads

Body-head connection M30 x 1,5

Nominal pressure PN10

Max. delta P 1 bar

Kvs value 1,08

Pre-settable yes

Features

- Easy, stepless adjustment of flow rates by standard 7mm wrench or by a setting key (see Accessories)
- Nominal flow up to 320kg/h with 2K p-band of the highstroke heads
- Quiet operation
- Strong restoring spring, which is not immersed in water, ensuring durability of the valve
- Double o-ring seal for maintenance-free operation
- Standard dimensions per EN215
- Standard M30 x 1.5 thermostat connection
- Valves can be shut-off with the protection cap
- V2000LX valves are compatible with the following Honeywell Home actuators: All radiator thermostats with M30 x 1.5 Connection, HR types of Evohome and Roomtronic actuators, MT4 actuators, M5410 2-point actuators, M4410E/K and M7410E5001 modulating actuators
- The valve insert can be replaced while the system is operating and without draining using the service tool (see Accessories)
- Valve housing and insert fits to Honeywell Home ATConcept design, ensuring housing and insert cross compatibility with MNG, Honeywell and

Honeywell Home thermostatic valves produced by Resideo and its predecessors since 1974

Place in installation supply

Closing dimension 11,5 mm

Colour of protection cap green

Stroke 2,5 mm

Additional Descriptions

- Nominal flow 235kg/h with standard head, 320kg/h with high-stroke head.
- Suitable connections see 'Connections for Radiator Valves'.

Max. media temperature 120 °C