

SI-V25-M230-2POS

Technical Specifications Valve - VBI60.25-16T

- **Angular rotation**
 - 90 °
- **Leakage rate**
 - „Waterproof“ as per EN 60534-4 L/1, better than class 4
 - **Leakage rate bypass** < 1 % of kv value
- **DN**
 - 25
- **kv**
 - 16 m³/h
- **Medium**
 - Cooling water, Chilled water, Water with anti-freeze, Low-temperature
- **PN class**
 - PN 40
- **Connecting thread**
 - Rp 1 "
- **GQD..9AΔpmax**
 - 350 kPa
- **GSD..9AΔpmax**
 - 350 kPa
- **GMA../GLB..9EΔpmax**
 - 350 kPa
- **GLB..9EΔpmax**
 - 350 kPa
- **Material, valve body**
 - Dezincification resistant hot-pressed brass (DZR), CW602N
- **Material, inside set**
 - Dezincification resistant hot-pressed brass (DZR), CW602N, chromium-plated

Technical Specifications Actuator - GQD321.9A

- **Torque**
 - 2 Nm
- **Angular rotation**
 - 90 °
- **Power consumption**
 - 10 VA, 4.5 W
- **Positioning time**
 - Opening with motor: 30 s, Closing with spring: 15 s
- **Positioning signal**
 - 2-position
- **Spring return function**
 - Yes
- **Degree of protection**
 - IP40
- **Ambient temperature, operation**
 - -32...55 °C
- **Dimensions (W x H x D)**
 - 75 x 113 x 136 mm
- **Mounting position**
 - Upright to horizontal
- **Operating voltage**
 - AC 230 V