



ATC928G3xxx CENTRAL CONTROLLER

PRODUCT SPECIFICATION SHEET



The evohome Central Controller is a multi-zone controller providing independent time and temperature control for radiator or underfloor heating systems as well as stored domestic hot water.

The evohome Central Controller can be used in many different configurations. As multi-zone system offers great benefits for larger properties but a single zone thermostat can also be used in smaller properties or simply as a 'starter' configuration, before upgrading to zoning.

The sophisticated fuzzy logic control in combination with heating optimisation features such as optimum start/stop or delayed start ensures precise and efficient temperature control throughout entire house.

The easy-to-use system interface provides access to all system functions through attractive colour touch screen display.

The evohome Central Controller can also be remotely accessed via the integrated Wifi and Android or iOS mobile apps.

FEATURES

- Independent time and temperature control of up to 12 heating zones and stored hot water
- Backlight colour LCD touch screen display
- Suitable for wall mounting (with in-wall power supply) or table top mounting on a stand provided
- 'Armchair' configuration and programming possible due to rechargeable batteries
- Optional front cover colours are available
- Informative home screen providing quick overview of system zones
- Quick actions buttons supporting most often used system override functions: away mode, economy mode, day-off more and system off mode provided as standard
- A choice of programming methods including system guided programming wizard mode and intuitive timeline graphical display
- Compatible with wide range of accessories using wireless LAN technology
- Additional information on evohome system on: homecomfort.resideo.com

SPECIFICATIONS

Power supply	4VDC, ±0.2V, max 2.6W
Battery	2 x rechargeable battery AA 1,2V NiMH, 2000-2400 mAh
RF Frequency	ISM (868.0-870.0)MHz
Receiver Class	2
RF Communication Range	30 m within a building
Display	LCD colour graphic 96 x 56 mm display area 480x272 pixel, 24 bit colour
Temperature Sensor	NTC, op. range 0 to 40°C
Operating Temperature	0 to 40°C
Humidity	10-90% RH non-cond.
Shipping & Storage	-20 to 50°C
Dimensions	139 x 101 x 21mm
IP Ratings	IP30
Standards	CE approved. EMC 2014/30/EU LVD 2014/35/EU RED 2014/53/EU RoHS 2011/65/EU

ORDERING SPECIFICATION

OS Number	Description	Target Markets
ATC928G3000	Central Controller Controller unit + instruction set	UK/NL/FR/BE
ATC928G3026	Central Controller Controller unit + instruction set	CZ/HU/PL/RO/SK/DA
ATC928G3027	Central Controller Controller unit + instruction set	DE/IT/ES



www.resideo.com

Ademco 1 GmbH
Hardhofweg 40
74821 Mosbach
Phone: +49 1801 466 388
info.de@resideo.com
[homecomfort.resideo](http://homecomfort.resideo.com)

@2020 Resideo Technologies, Inc. All rights reserved The Honeywell Home trademark is used under license from Honeywell International Inc. This product is manufactured by Resideo Technologies, Inc and its affiliates.



Strandvejen 42 ♦ Saksild ♦ 8300 Odder
86 62 63 64 ♦ www.automatikcentret.dk
info@automatikcentret.dk

Honeywell Home